FUJI
innovative spirit

Auto Splicing Unit

Automation of splicing work
Anyone can splice easily and accurately

- **Easy operation**
  Simply insert old and new tape in either side of unit
- **Accurate splicing regardless of operator skill level**
- **Faster than manual work**
  Splicing completed in about 5 seconds

Linked to Fuji system

Supporting software

Splicing warnings from Kit Handy (Fujitrax Verifier)

The number of parts used is counted by the system and operators are given warnings before parts run out. The operator resupplies parts based on the display and prevents production stoppages due to parts running out.

Basic specifications

Supported tape types	8 mm paper tape
Part size	0402 (01005") to 3216 (1206") (3.2 x 2.5 mm)
Splicing tape	Fuji splicing tape (reel type, 1200 pieces per reel)
Tape connection position accuracy	±0.2 mm
Cycle time	5.3 sec
Unit size	450 x 450 mm x H1002 mm (±100 mm)
Power supply	Rechargeable battery (Input voltage: AC 100 to 240V)

Fuji Machine Mfg. Co., Ltd.

http://www.fuji.co.jp

19 Chausuyama Yamamachi Chiryu-shi, Aichi-ken 472-8686 Japan
Tel: +81-566-81-2110 Fax: +81-566-83-1140

- The contents of this catalog are subject to change without notice.
- Contact Fuji or a Fuji representative before transporting this product to a foreign location within your company or selling it to a third party within your country or a different country.
- The information in this catalog is current as of April, 2014.

© 2014 FUJI MACHINE MFG. CO., LTD. All Rights Reserved.

Cat.No.Auto Splicing Unit_2014_Apr_E